

Module lights directly replace of traditional incandescent bulbs, with E27 base. The module allows the use of LED technology without renewal of the frame of the signal , drastically reducing the cost of renovation and installation.



Features Highlight:

1. **5 degrees Lens:** The LED light beam expands with its optical lens.
2. **High Brightness:** Use of the highest quality of LED components.
3. **Long Working life:** over 50,000 hours
4. **Automatic Sensor (optional):** Automatic adjustment of LED brightness according to ambient light
5. **Energy Savings:** With its low power consumption can save between 80 and 90% of energy.
6. **Certificates:** CE, ITE, GB14887-2003 Standards
7. **Protection:** IP65

Module lights direct replacement of traditional incandescent bulbs, wire bonding. The module allows the use of LED technology without renewal of the frame of the signal, dramatically reducing the cost of renovation and installation.



Features Highlight:

1. **5 degrees Lens:** The LED light beam expands with its optical lens.
2. **High Brightness:** Use of the highest quality of LED components.
3. **Long Working life:** over 50,000 hours
4. **Automatic Sensor (optional):** Automatically adjusts LED brightness based on ambient light
5. **Energy Savings:** With its low power consumption can save between 80 and 90% of energy.
6. **Certificates:** CE, ITE, GB14887-2003 Standards
7. **Protection:** IP65

LED E27 Traffic Light Bulbs / Wiring 200mm



Picture	Model	Color	LED Qty	Intensity (cd)	Wavelength (nm)	Visual Angle		Power Consumption
						Left/Right	Down	
	SE001-R	Red	90	≥400	625±5	60	20	≤8
	SE001-A	Amber	90	≥400	590±5	60	20	≤8
	SE001-V	Green	90	≥400	505±2	60	20	≤9
	SE002-R	Red	38	≥4,000/m2	625±5	30	10	≤5
	SE002-A	Amber	38	≥4,000/m2	590±5	30	10	≤5
	SE002-V	Green	38	≥4,000/m2	505±2	30	10	≤5
	SE003-R	Red	36	≥4,000/m2	625±5	30	10	≤5
	SE004-R	Red	68	≥4,000/m2	625±5	30	10	≤5
	SE004-V	Green	62	≥4,000/m2	505±2	30	10	≤6
	SE005-V	Green	314	≥4,000/m2	505±2	30	10	≤10

Temperature Operation : -40°C a +80°C

Voltage: 80-280V AC 50-60HZ

Diameter: Ø214mm

Packing: 1 Pc/Box, 10 Pcs./Carton(1020x250x250mm)

Net Weight / Gross:7,5 Kg / 9Kg

Quantity 20 feet: 4.590 units

Quantity 40 feet: 9.450 units

LED E27 Traffic Light Bulbs / Wiring 300mm



Picture	Model	Color	LED Qty	Intensity (cd)	Wavelength (nm)	Visual Angle		Power Consumption
						Left/Right	Down	
	SE011-R	Red	168	≥800	625±5	60	20	≤12
	SE011-A	Amber	168	≥800	590±5	60	20	≤12
	SE011-V	Green	168	≥800	505±2	60	20	≤13
	SE012-R	Red	65	≥4,000/m2	625±5	60	20	≤7
	SE012-A	Amber	65	≥4,000/m2	590±5	60	20	≤7
	SE012-V	Green	65	≥4,000/m2	505±2	60	20	≤7
	SE013-R	Red	93	≥4,000/m2	625±5	30	10	≤5
	SE014-R	Red	80	≥4,000/m2	625±5	30	10	≤7
	SE014-V	Green	78	≥4,000/m2	505±2	30	10	≤8
	SE015-V	Green	314	≥4,000/m2	505±2	30	10	≤10
	SE016-R	Red	76	≥4,000/m2	625±5	60	20	≤8
	SE016-A	Amber	76	≥4,000/m2	505±2	60	20	≤8
	SE016-V	Green	76	≥4,000/m2	505±2	60	20	≤8
	SE017-RV	Red + Green	93	≥4,000/m2	625±5	30	10	≤8
			75	≥4,000/m2	505±2	30	10	

Temperature Operation : -40°C a +80°C

Voltage: 80-280V AC 50-60HZ

Diameter: Ø303mm

Packing: 1 Pcs/Box, 10 Pcs./Carton(1500x335x335mm)

Net Weight / Gross:13,5 Kg / 20Kg

Quantity 20 feet:1.540 unidades

Quantity 40 feet:3.221 unidades

